


TENUS ROUND SNOOT

TRN 09 30 60 CL 85 TL WWB




Artech Tenus Round Snoot Fixed Downlight

Artech Tenus recessed architectural fixed LED downlight with ingress protection IP44. Total luminous flux up to 900lm with overall luminaire efficacy of 87 lm/W. Supplied with fixed output, DALI digital or phase-cut dimmable driver, optional 3 -hour Basic or EMPRO emergency kit. Forged aluminum heat sink with die-cast white or black bezel.



Mounting	Recessed (Trimless)
Lamp Type	LED
Wattage	10.4 W
Lumen Output	900 lm
Efficacy	87 lm/W
Colour Temperature	3000 K
CRI	90+
Beam Angle	60°
IP Rating	IP44
Control Gear	Fixed Output
Dimensions	111 Dia x 87 mm
Colour Finish	White/ White/ Black
MacAdam	3
Service Lifetime	L80/B10- 55,000 Hrs



powered by

TRIDONIC

Driver details available upon request



Artech lighting strives to ensure all solutions are supplied with the latest technology, we therefore reserve the right to make technical and design changes without prior notice. Electrical connected load and luminous flux are subject to initial tolerance of up +/- 10%. Colour Temperature is subject to a tolerance of +/-150 Kelvin

St. Johns Rd, Meadowfield Industrial Estate, Durham, Co. Durham, DH78RJ - United Kingdom | T: +44(0)1913787960 - F: +44(0)1913787909 - www.artechlighting.com

