

ARTECH  
LIGHTING

# HIGHLIGHT SLIM



YOUR PROJECT,  
YOUR CHOICE



## HIGHLINE SLIM PART CODES EXPLAINED

Part Code e.g: **AHS 157 40 90 G S W D**



**AHS**

Product



**57**

Lumen




**40**

Temperature



**90**

Distribution Optics



**G**

Size



**S**

Mounting Method



**W**

Colour

## ORDERING GUIDE

### Product

**AHS** Highline Slim

### Lumen Output

**25** 2530 Lumen   **34** 3438 Lumen   **46** 4584 Lumen   **57** 5730 Lumen  
**69** 6876 Lumen   **80** 8022 Lumen   **92** 9168 Lumen   **103** 10314 Lumen  
**114** 11460 Lumen

### Temperature

**30** 3000 Kelvin   **40** 4000 Kelvin

### Distribution Optics

**60** 60°   **90** 90°

### Size

**G** 1690mm\*

### Mounting Method

**S** Surface   **P** Pendant

### Colour

**W** White

### Options

**D** DALI   **DEP** DALI Empro   **DE3** DALI 3HR Emergency   **DST** DALI Self Test  
**E3** 3HR Emergency   **EP** Empro   **ST** Self Test

**Custom Solutions:** Variation for product solutions available upon request.

\*Complete size range available.



A surface mounted or suspended solution, the Highline Slim allows high output lighting across various applications. The product offers highly efficient LED Lighting with impact resistant aluminium frame and polycarbonate diffuser. The Highline Slim is also available as a continuous system, with optional microwave sensors, end caps and through wiring infills.

## DIMENSIONS



## CONTINUOUS OPTION

