


TENUS 90

ARTECH
LIGHTING

Part Code: **TRF 09 30 60 CL 90 P BB**



Artech Tenus pendant architectural fixed LED downlight with ingress protection IP44. Total luminous flux up to 3000 lm with overall luminaire efficacy of 100 lm/W. Supplied with fixed output, DALI digital or phase-cut dimmable driver, optional 3-hour Basic or EMPRO emergency kit. Forged aluminum heat sink with die-cast white or black bezel.



Production Information

–

Physical

Mounting Type – Pendant
Length – 270mm
Diameter – 90mm
Finish – Black/Black
IP Rating – IP44

–

Electrical

Lamp Type – LED
Wattage – 9 W
Efficacy – 100lm/W
Driver – Tridonic/Forge
Control – Fixed Output

–


LED

Manufacturer – Phillips Lumileds
LED Type – COB 120s
Delivered lumen output – 900lm
CCT – 3000K
CRI – 90+
MacAdam – < 3
Service Lifetime – L80/B10 55,000hrs

–

Optic

60° Beam Angle/ Clear Optic



Artech lighting strives to ensure all solutions are supplied with the latest technology, we therefore reserve the right to make technical and design changes without prior notice. Electrical connected load and luminous flux are subject to initial tolerance of up +/- 10%. Colour Temperature is subject to a tolerance of +/-150 Kelvin.

St Johns Rd, Meadowfield Ind. Estate, Durham, Co. Durham, DH7 8RJ, United Kingdom
T: +44(0) 191 3787960 E: info@artechlighting.com

Powered by:

TRIDONIC

**MADE IN
BRITAIN UK
CA**