


# TENUS 205

ARTECH  
LIGHTING

Part Code: **TRF 14 40 90 CL 205 S BB D**



Artech Tenus surface architectural fixed LED downlight with ingress protection IP44. Total luminous flux up to 5000 lm with overall luminaire efficacy of 125 lm/W. Supplied with fixed output, DALI digital or phase-cut dimmable driver, optional 3-hour Basic or EMPRO emergency kit. Forged aluminum heat sink with die-cast white or black bezel




## Production Information

–  
**Physical**  
Mounting Type – Surface  
Height – 210mm  
Diameter – 205mm  
Finish – Black/Black  
IP Rating – IP44

–  
**Electrical**  
Lamp Type – LED  
Wattage – 11.4 W  
Efficacy – 125 lm/W  
Driver – Tridonic/Forge  
Control – DALI

–  
**LED**  
Manufacturer – Phillips Lumileds  
LED Type – COB 1210  
Delivered lumen output – 1430lm  
CCT – 4000K  
CRI – 90+  
MacAdam – < 3  
Service Lifetime – L80/B10 55,000hrs

–  
**Optic**  
90° Beam Angle/ Clear Optic



Artech lighting strives to ensure all solutions are supplied with the latest technology, we therefore reserve the right to make technical and design changes without prior notice. Electrical connected load and luminous flux are subject to initial tolerance of up +/- 10%. Colour Temperature is subject to a tolerance of +/-150 Kelvin.

**St Johns Rd, Meadowfield Ind. Estate, Durham, Co. Durham, DH7 8RJ, United Kingdom**  
**T: +44(0) 191 3787960 E: info@artechlighting.com**

Powered by:

**TRIDONIC**

**MADE IN  
BRITAIN UK  
CA**