


TENUS 205

ARTECH
LIGHTING

Part Code: **TRF 50 40 90 CL S WW**



Artech Tenus surface architectural fixed LED downlight with ingress protection IP44. Total luminous flux up to 5000 lm with overall luminaire efficacy of 125 lm/W. Supplied with fixed output, DALI digital or phase-cut dimmable driver, optional 3-hour Basic or EMPRO emergency kit. Forged aluminum heat sink with die-cast white or black bezel




Production Information

–
Physical
Mounting Type – Surface
Height – 210mm
Diameter – 205mm
Finish – White/White
IP Rating – IP44

–
Electrical
Lamp Type – LED
Wattage – 40 W
Efficacy – 125 lm/W
Driver – Tridonic/Forge
Control – DALI

–
LED
Manufacturer – Phillips Lumileds
LED Type – COB 1210
Delivered lumen output – 5000lm
CCT – 4000K
CRI – 90+
MacAdam – < 3
Service Lifetime – L80/B10 55,000hrs

–
Optic
90° Beam Angle/ Clear Optic



Artech lighting strives to ensure all solutions are supplied with the latest technology, we therefore reserve the right to make technical and design changes without prior notice. Electrical connected load and luminous flux are subject to initial tolerance of up +/- 10%. Colour Temperature is subject to a tolerance of +/-150 Kelvin.

St Johns Rd, Meadowfield Ind. Estate, Durham, Co. Durham, DH7 8RJ, United Kingdom
T: +44(0) 191 3787960 E: info@artechlighting.com

Powered by:

TRIDONIC

**MADE IN
BRITAIN UK
CA**