


TENUS 90

ARTECH
LIGHTING

Part Code: **TRF 20 40 60 CL 90 S BB**



Artech Tenus surface architectural fixed LED downlight with ingress protection IP44. Total luminous flux up to 3000 lm with overall luminaire efficacy of 100 lm/W. Supplied with fixed output, DALI digital or phase-cut dimmable driver, optional 3-hour Basic or EMPRO emergency kit. Forged aluminium heat sink with die-cast white or black bezel.




Production Information

–
Physical
Mounting Type – Surface
Length – 270mm
Diameter – 90mm
Finish – Black/Black
IP Rating – IP44

–
Electrical
Lamp Type – LED
Wattage – 20 W
Efficacy – 100lm/W
Driver – Tridonic/Osram
Control – Fixed Output

–
LED
Manufacturer – Phillips Lumileds
LED Type – COB 120s
Delivered lumen output – 2000lm
CCT – 4000K
CRI – 90+
MacAdam – <3
Service Lifetime – L80/B10 55,000hrs

–
Optic
60° Beam Angle/ Clear Optic



Artech lighting strives to ensure all solutions are supplied with the latest technology, we therefore reserve the right to make technical and design changes without prior notice. Electrical connected load and luminous flux are subject to initial tolerance of up +/- 10%. Colour Temperature is subject to a tolerance of +/-150 Kelvin.

St Johns Rd, Meadowfield Ind. Estate, Durham, Co. Durham, DH7 8RJ, United Kingdom
T: +44(0) 191 3787960 E: info@artechlighting.com