


# TENUS 90

ARTECH  
LIGHTING

Part Code: **TRT 05 40 60 CL 90 S BB**



Tenus 90 is an elegant directional surface spotlight, with high quality aluminium housing and discrete hinge design allowing for concise adjustment. Total luminous flux up to 3000 lm with overall luminaire efficacy of 100 lm/W. Supplied with fixed output, DALI digital or phase-cut dimmable driver, optional 3 -hour Basic or EMPRO emergency kit. Forged aluminium heat sink with die-cast white or black bezel.




## Production Information

–  
**Physical**  
Mounting Type – Surface  
Length – 192mm  
Diameter – 90mm  
Finish – Black/Black  
IP Rating – IP20

–  
**Electrical**  
Lamp Type – LED  
Wattage – 5 W  
Efficacy – 100lm/W  
Driver – Tridonic/Osram  
Control – Fixed Output

–  
**LED**  
Manufacturer – Phillips Lumileds  
LED Type – COB 1280  
Delivered lumen output – 500lm  
CCT – 4000K  
CRI – 90+  
MacAdam – <3  
Service Lifetime – L80/B10 55,000hrs

–  
**Optic**  
60° Beam Angle/ Clear Optic



Artech lighting strives to ensure all solutions are supplied with the latest technology, we therefore reserve the right to make technical and design changes without prior notice. Electrical connected load and luminous flux are subject to initial tolerance of up +/- 10%. Colour Temperature is subject to a tolerance of +/-150 Kelvin.

St Johns Rd, Meadowfield Ind. Estate, Durham, Co. Durham, DH7 8RJ, United Kingdom  
T: +44(0) 191 3787960 E: info@artechlighting.com

MADE IN  
BRITAIN UK  
CA