


Part Code: **APL 100 40 PC C S**



Artech Prolight architectural LED luminaire with ingress protection IP66. Total luminous flux up to 11,385 lm with overall luminaire efficacy up to 158 lm/W. Supplied with fixed output, DALI digital dimmable driver, optional 3 – hour Basic or EMPRO emergency kit. Steel housing with polycarbonate diffuser.




Production Information

– **Physical**
 Mounting Type – Surface
 Length – 1515mm
 Height – 75mm
 Width – 116mm
 Finish – Grey
 IP Rating – IP66

– **Electrical**
 Lamp Type – LED
 Wattage – 62 W
 Efficacy – 161 lm/W
 Driver – Tridonic/Osram
 Control – Fixed Output

– **LED**
 Manufacturer – Light Engines Europe
 LED Type – LEE-LINEAR-24-STD-SAM
 LED Pitch – 9.33mm
 Delivered lumen output – 9962 lm
 CCT – 4000K
 CRI – 80+
 MacAdam – 3
 Service Lifetime – L80/B10 81,000hrs

– **Optic**
 Polycarbonate



Artech lighting strives to ensure all solutions are supplied with the latest technology, we therefore reserve the right to make technical and design changes without prior notice. Electrical connected load and luminous flux are subject to initial tolerance of up +/- 10%. Colour Temperature is subject to a tolerance of +/-150 Kelvin.

St Johns Rd, Meadowfield Ind. Estate, Durham, Co. Durham, DH7 8RJ, United Kingdom
T: +44(0) 191 3787960 E: info@artechlighting.com