


Part Code: **NAI 1700 120 30 10 67**



Artech flexible LED strip is architectural solution for cove lighting or edge lighting, with 3000K Colour temperature. Total luminous flux up to 1700 lm/m with overall luminaire efficacy up to 118 lm/W. Low heat and low maintenance costs. White PVC base edge to increase luminosity.




Production Information

–
Physical
 Max Length – 10,000mm
 Cut Point – 50mm
 Width – 10mm
 Finish – White
 IP Rating – IP67
 LEDs p/m – 120 LEDs p/m

–
Electrical
 Lamp Type – LED
 Wattage – 14.4 W/m
 Efficacy – 118 lm/W
 Input Voltage – 24 V

–
LED
 LED Type – SMD2835
 Delivered lumen output – 1700lm/m
 CCT – 3000K
 CRI – 90+
 MacAdam – < 3
 Service Lifetime – L80/B10 50,000 Hrs

–
Optic
 120° Beam Angle



Artech lighting strives to ensure all solutions are supplied with the latest technology, we therefore reserve the right to make technical and design changes without prior notice. Electrical connected load and luminous flux are subject to initial tolerance of up +/- 10%. Colour Temperature is subject to a tolerance of +/-150 Kelvin.

St Johns Rd, Meadowfield Ind. Estate, Durham, Co. Durham, DH7 8RJ, United Kingdom
T: +44(0) 191 3787960 E: info@artechlighting.com