


TENUS 40 ROUND FIX

ARTECH
LIGHTING

Part Code: TRF 03 40 38 CL 40 ST W D



Artech Tenus recessed architectural fixed LED downlight with ingress protection IP20. Total luminous flux up to 260 lm with overall luminaire efficacy of 87 lm/W. Supplied with fixed output, DALI digital or phase-cut dimmable driver, optional 3-hour Basic or EMPRO emergency kit. Forged aluminium heat sink with die-cast white or black bezel.



Production Information

Physical

Mounting Type – Recessed (With Trim)
Height – 58mm
Diameter – 40mm
Cutout – 35mm
Finish – White
IP Rating – IP20

Electrical


Lamp Type – LED
Wattage – 3W
Efficacy – 87 lm/W
Driver – Tridonic/Osram
Control – DALI2 - Remote Access Required

LED

Manufacturer – CREE
LED Type – CXB1304
Delivered lumen output – 260lm
CCT – 4000K
CRI – 80+
MacAdam – < 3
Service Lifetime – L80/B10 55,000hrs

Optic

38° Beam Angle/ Clear Optic



Artech lighting strives to ensure all solutions are supplied with the latest technology, we therefore reserve the right to make technical and design changes without prior notice. Electrical connected load and luminous flux are subject to initial tolerance of up +/- 10%. Colour Temperature is subject to a tolerance of +/-150 Kelvin.

St Johns Rd, Meadowfield Ind. Estate, Durham, Co. Durham, DH7 8RJ, United Kingdom
T: +44(0) 191 3787960 E: info@artechlighting.com

MADE IN
BRITAIN UK
CA