


TENUS 197

ARTECH
LIGHTING

Part Code: **TRF 34 40 90 CL 197 ST WW D**



Artech Tenus recessed architectural fixed LED downlight with ingress protection IP44. Total luminous flux up to 3360 lm with overall luminaire efficacy of 125 lm/W. Supplied with fixed output, DALI digital or phase-cut dimmable driver, optional 3-hour Basic or EMPRO emergency kit. Forged aluminium heat sink with die-cast white or black bezel.



Production Information

Physical

Mounting Type – Recessed (With Trim)
Height – 141mm
Diameter – 197mm
Cutout – 185mm
Finish – White/White
IP Rating – IP44

Electrical


Lamp Type – LED
Wattage – 26.8 W
Efficacy – 125 lm/W
Driver – Tridonic/Osram
Control – DALI2

LED

Manufacturer – Phillips Lumileds
LED Type – COB 1208
Delivered lumen output – 3360lm
CCT – 4000K
CRI – 80+
MacAdam – < 3
Service Lifetime – L80/B10 55,000hrs

Optic

90° Beam Angle/ Clear Optic



Artech lighting strives to ensure all solutions are supplied with the latest technology, we therefore reserve the right to make technical and design changes without prior notice. Electrical connected load and luminous flux are subject to initial tolerance of up +/- 10%. Colour Temperature is subject to a tolerance of +/-150 Kelvin.

St Johns Rd, Meadowfield Ind. Estate, Durham, Co. Durham, DH7 8RJ, United Kingdom
T: +44(0) 191 3787960 E: info@artechlighting.com

MADE IN
BRITAIN UK
CA