PROLIGHT 3

Part Code: **AP3 100 40 PC B S D**

Artech Prolight architectural LED luminaire with ingress protection IP66. Total luminous flux up to 11,385 lm with overall luminaire efficacy up to 158 lm/W. Supplied with fixed output, DALI digital dimmable driver, optional 3 – hour Basic or EMPRO emergency kit. Steel housing with polycarbonate diffuser.



PRODUCTION INFORMATION

–

Physical
Mounting Type – Surface
Length – 1500mm
Height – 101mm
Width – 101mm
Finish – Grey
IP Rating – IP65

–

Electrical
Lamp Type – LED
Wattage – 62W
Efficacy – 158lm/W
Driver – Tridonic/Osram
Control – DALI2

–

LED
Manufacturer – Light Engines Europe
LED Type – LEE-LINEAR-24-STD-SAM
LED Pitch – 9.33mm
Delivered lumen output – 9962 lm
CCT – 4000K
CRI – 80+
MacAdam – 3
Service Lifetime – L80/B10 81,000hrs

–

Optic
Polycarbonate



Artech lighting strives to ensure all solutions are supplied with latest technology, we therefore reserve the right to make technical and design changes without prior notice. Electrical connected load and luminous flux are subject to initial tolerance of up +/- 10%. Colour Temperature is subject to a tolerance of +/-150 Kelvin

St Johns Rd, Meadowfield Ind. Estate, Durham, Co. Durham, DH7 8RJ, United Kingdom
T: +44(0) 191 378 7960 E: info@artechlighting.com

MADE IN BRITAIN UK CA CE